

REMARKS

The present amendment makes editorial changes and corrects typographical errors in the specification, which includes the Abstract, in order to conform the specification to the requirements of United States Patent Practice. No new matter is added thereby. Attached hereto is a Substitute Specification including a marked-up version of the changes made thereto via by the present amendment.


In addition, the present amendment cancels original claims 1-6 in favor of new claims 7-12. Claims 7-12 have been presented solely because the revisions by red-lining and underlining which would have been necessary in claims 1-6 in order to present those claims in accordance with preferred United States Patent Practice would have been too extensive, and thus would have been too burdensome. The present amendment is intended for clarification purposes only and not for substantial reasons related to patentability pursuant to 35 U.S.C. §§101, 102, 103 or 112. Indeed, the cancellation of claims 1-6 does not constitute an intent on the part of the Applicants to surrender any of the subject matter of claims 1-6.

Early consideration on the merits is respectfully requested.

Respectfully submitted,

BELL, BOYD & LLOYD LLC

BY



Peter Zura

Reg. No. 48,196

P.O. Box 1135

Chicago, Illinois 60690-1135

Phone: (312) 807-4208

Dated: May 9, 2005

Marked-Up Version of Substitute Specification

Description

~~Communication terminal with configured bandwidth expansion, and a method for bandwidth expansion for this purpose~~

SPECIFICATION

TITLE OF THE INVENTION

COMMUNICATION TERMINAL WITH CONFIGURED BANDWIDTH
EXPANSION, AND A METHOD FOR BANDWIDTH EXPANSION FOR THIS
PURPOSE

FIELD OF TECHNOLOGY

The ~~invention~~ present disclosure relates to a communication terminal with a bandwidth expansion device for expansion of a bandwidth of a narrowband speech signal at its low-frequency and/or high-frequency end by synthesis of at least one frequency band on the basis of the narrowband speech signal.

BACKGROUND

For mobile telephones that are currently on the market, as examples of communication terminals, the relevant GSM Standard specifies that a standard net bit rate be used for the speech coder which carries out the function of coding of speech signals to form reduced-data narrowband speech signals, which are transmitted via a transmission output stage of the communication terminal. The GSM-specific net bit rate is 12.2 kbit/s, and relates, ~~for example,~~ generally to the widely used EFR Codec. Further developments of the EFR Codec have the aim, however, of making it possible to process different net bit rates for the speech coder. In this context, the NBAMR Codec ("Narrowband Adaptive Multirate") ~~should be mentioned,~~ is commonly used which, overall, allows eight different net bit rates for operation of the speech coder, ~~specifically the net bit rates~~ (4.75; 5.15; 5.9; 6.7; 7.4; 7.95; 10.2 and 12.2 kbit/s). In this case, the expectation from the lower net bit rates is that they will actually have advantages for comparatively poor radio transmission paths, since the transmitted signals can be provided with greater redundancy.

The measure of providing a communication terminal with a bandwidth expansion device which evaluates a narrowband speech signal (which has been received by the communication terminal) and synthesizes at least one further frequency band on the basis of the evaluation by means of a suitable algorithm is likewise known from the prior art. Normally, the currently used narrowband speech signal is in the frequency band between 300 Hz and 3.4 kHz. Additional frequency bands can be produced by synthesis both at the low-frequency end and at the high-frequency end of this frequency band, thus resulting in bandwidth expansion. Communication terminals such as this with bandwidth expansion have, however, so far been proposed only in conjunction with speech coders which operate at a single net bit rate.

BRIEF SUMMARY

Against this background, ~~the invention is based on the object of providing~~ present disclosure provides a communication terminal in which qualitatively satisfactory bandwidth expansion can be carried out even when using two or more net bit rates for the narrowband speech signal under an exemplary embodiment. A further ~~aim is to specify~~ embodiment discloses a method for expansion of a bandwidth of a narrowband speech signal for a communication terminal, which can be used with communication terminals which operate with two or more net bit rates for the narrowband speech signal.

~~With regard to the communication terminal, the object is achieved by a~~ The communication terminal is preferably equipped with a bandwidth expansion device for expansion of a bandwidth of a narrowband speech signal at its low-frequency and/or high-frequency end by synthesis of at least one frequency band on the basis of the narrowband speech signal, ~~the~~ The bandwidth expansion device being is also connected to a memory in which a reference table is stored, which in each case contains at least one parameter value for the bandwidth expansion for at least two net bit rates of the narrowband speech signal.

A memory ~~which that~~ contains values that are suitable for the respectively used net bit rates for parameters which govern the quality of the bandwidth expansion is thus provided for the novel communication terminal. ~~This method is~~

~~based on the discovery by the inventors that~~ The optimum configuration for the bandwidth expansion may be dependent on which net bit rate is currently being used by a speech coder on which the received narrowband speech signal is based. The memory is provided for this reason and contains, for example, empirically determined values for the parameters, in which case auditory tests can in each case be carried out for the respective net bit rates.

~~In one preferred~~ Under one embodiment, the reference table ~~which that~~ is stored in the memory takes account, as parameters for bandwidth expansion, of the energy in a synthesized frequency band and of a spectral structure of the synthesized frequency band. This means that the reference table is used to store, for a respective net bit rate, values which make it possible to deduce the energy in a synthesized frequency band, while a second parameter value defines the spectral structure of the synthesized frequency band.

~~By way of~~ As an example, the energy in a synthesized frequency band may be rather low when the net bit rate is comparatively low, since, in this case, the probability of artefacts occurring in the narrowband speech signal is rather high. Fundamentally, artefacts in the narrowband speech signal lead to errors in the synthesized frequency band, since the synthesis is based on evaluation of the narrowband speech signal. It may therefore be advantageous to keep the total energy in the synthesized frequency band low when the bit rate is low.

The probability of occurrence of artefacts can also be taken into account in terms of the spectral structure of the synthesized frequency band. Provided that these artefacts are localized sufficiently well within one frequency band of the narrowband speech signal, a low intensity can be provided in the synthesized frequency band for those frequencies which are based on frequency components in the narrowband speech signal that are subject to artefacts.

With regard to ~~the a~~ method disclosed herein, ~~the object mentioned above is achieved by a method for performs~~ expansion of the bandwidth of a narrowband speech signal for a communication terminal, having the following steps under an alternate embodiment:

- a) ~~detection of~~detecting a net bit rate of the narrowband speech signal of the communication terminal,
- b) ~~access to~~accepting a memory which contains a reference table which contains associations between at least two net bit rates and parameter values for bandwidth expansion, in order to determine the at least one parameter value which is suitable for the detected net bit rate.
- c) ~~expansion of the~~expanding bandwidth by means of a bandwidth expansion device on the basis of the parameters determined for a current bit rate in step b).

This exemplary method takes account of the fact that, for example, over the course of a communication link, it is also possible for a change to occur from a first net bit rate to a second net bit rate for a speech coder which is producing the narrowband speech signal. For this reason, the current net bit rate of the speech coder is detected in the step a), so that the appropriate values for the parameters for bandwidth expansion can be found on the basis of this net bit rate in step b). The bandwidth expansion can then be carried out as well as possible in step c) on the basis of the results from step b).

~~Preferred embodiments of the method are specified in claims 4 to 6, whose subject matters have already been explained above with reference to the description of the communication terminal.~~

BRIEF DESCRIPTION OF THE DRAWINGS

The various objects, advantages and novel features of the present disclosure will be more readily apprehended from the following Detailed Description when read in conjunction with the enclosed drawings, in which

~~The invention will be explained in more detail in the following text using, by way of example, the single drawing figure, which shows~~ Figure 1 illustrates a schematic block diagram of a communication terminal.

DETAILED DESCRIPTION

As can be seen from ~~the figure~~ Figure 1, speech signals in a mobile communication terminal pass on a transmission side from a microphone 1 to a speech coder 2 which is used for compression of the data transmission rate. The speech coder 2 operates on the basis of ~~the a~~ a "Linear Predictive Coding" (LPC)

method, which simulates the process of creating a speech signal at the human speech rate. The speech coder 2 operates at various net bit rates, to be precise at that net bit rate which is defined on the network side for the transmitting communication terminal, and at the same time for a receiving mobile communication terminal. This definition covers both radio paths from the transmitting mobile communication terminal via the network structures that are involved to the receiving mobile communication terminal with which a communication link is to be set up. The net bit rate may, for example, change in the event of a deterioration occurring over the course of the communication link, such that it is reduced to a lower value.

On the network side, a processor 3 in the mobile communication terminal ~~according to the invention~~ receives information on the net bit rate that is currently to be used for the link between the two mobile communication terminals. Depending on this information, the processor 3 accesses a memory 4 in which a reference table is stored, which contains all the possible net bit rates for the speech coder 2 and in each case includes associated values for at least the major parameters for bandwidth expansion, which is carried out by means of a bandwidth expansion device 5.

In practice, there are further functional components connected between the speech coder 2 at the transmission end and the bandwidth expansion device 5 at the receiving end which, inter alia, also carry out the radio transmission of the coded speech signals, although this is not illustrated in the figure, for clarity reasons.

The ~~major~~ main parameters for bandwidth expansion are, for example, the total energy in an additional frequency band which is synthesized by means of a bandwidth expansion device 5 and is, for example, at the high-frequency end of the narrowband speech signal, which must be passed back to the speech coder 2. A further ~~important~~ parameter is the spectral distribution of the intensities in the synthesized frequency band.

Both the main parameters which have been mentioned for bandwidth expansion take account of the fact that artefacts may in fact occur at low bit rates in the narrowband speech signal and affect the synthesized frequency band, as well, in

the course of the bandwidth expansion process. In general, it can be assumed that the probability of artefacts in the narrowband speech signal is rather high at a low bit rate. Against this background, when the bit rates are low, not only is the total energy in the synthesized frequency band low, but the synthesized frequency band is also spectrally weighted such that frequency intervals are weighted as being low for which there is a high probability of the presence of artefacts in the associated frequency interval in the narrowband frequency band of the speech signal.

An output signal from the bandwidth expansion device 5 which comprises both the narrowband speech signal and a synthesized frequency band resulting from the bandwidth expansion is passed to a loudspeaker 6, via which speech signals are emitted.

The above described description and drawings are only to be considered illustrative of exemplary embodiments, which achieve the features and advantages of the invention. Modifications and substitutions to specific process conditions and structures can be made without departing from the spirit and scope of the invention. Accordingly, the invention is not to be considered as being limited by the foregoing description and drawings, but is only limited by the scope of the appended claims.

ABSTRACT

The ~~invention~~ disclosure relates to a communication terminal ~~comprising~~ having a bandwidth expansion device (5) for expanding the bandwidth of a narrowband voice signal, on a low-frequency and/or high-frequency side, by synthesizing at least one frequency band on the basis of the narrowband voice signal. ~~The aim of the invention is to carry out a~~ A qualitatively satisfactory bandwidth expansion is thus performed using a plurality of net bit rates. ~~To this end~~ The bandwidth expansion device (5) is further connected to a memory (4) containing a lookup table comprising at least one parameter value for the bandwidth expansion, for at least two net bit rates of the narrowband voice signal. ~~The invention also relates to a~~ A method for expanding a bandwidth of a narrowband voice signal having at least two net bit rates in a communication terminal is also disclosed herein.